



C-GMA/GMA

VGA (15-Pin HD) +3.5mm Stereo Audio Cable



Kramer's GMA series are high-performance cables with male 15-pin HD and 3.5mm stereo audio connectors at each end. They are perfect for computer graphics video to display installations which require an audio signal as well.

FEATURES

- **Quality Construction** - Constructed using our rugged and flexible 14 conductor cable.
- **Easy Connection** - Pre-terminated with molded 15-pin HD connectors (male to male), gold plated pins and thumbscrews for easy connection and a 3.5mm stereo mini jack.
- **Easy Installation** - Audio leads extend 24in (61cm) beyond the 15-pin HD head at one end, and 8in (20cm) at the other.
- **Cable Specs** - See Kramer BC-3X2T7S for detailed cable specs.
- **Varied Selection of Lengths** - Available in 3, 6, 10, 15 and 25ft versions (0.9 to 7.6m).

TECHNICAL SPECIFICATIONS

| | |
|---------------------------|--|
| Attenuation (dB/100 ft.): | -0.5 dB @ 1MHz. -1.3 dB @ 5 MHz. -1.9 dB @ 10 MHz. -4.0 dB @ 50MHz. -5.7 dB @ 100MHz. -8.0 dB @ 180MHz. -14.0 dB @ 400MHz. |
| Conductor: | 26 AWG 7/34 tinned copper. |
| Dielectric: | Foam polyethylene with red, green, blue color coding. |
| Shield: | (A) 90% spiral 38 AWG tinned copper. (B) aluminum-foil/mylar 25% overlap rate. |
| Inner Jacket: | PVC. |
| Jacket Colors: | Black. |
| Outer Jacket Color: | Dark gray w/white lettering. |
| Outer Diameter: | 0.393 inches, 10.0mm. |
| UL: | CL2. |
| CSA: | C(UL) CL2. |
| Conductors: | 26 AWG 7/34 tinned copper. |
| Jacket: | HD-polyethylene. |
| Diameter: | 0.34 inch, 0.88mm. |
| Jacket Colors: | Red, orange, brown, yellow, black, red/black. |
| Shield: | (A) 85% braid 36 AWG tinned copper. (B) aluminum-foil/mylar 25% overlap rate. |



KRAMER ELECTRONICS, Ltd.

www.kramerelectronics.com

| | |
|-------------------|--|
| Outer Jacket: | PVC. |
| Temperature: | 68° to 167° fahrenheit, - 20° to 75° celsius. |
| Conductor: | 26 AWG 7/34 tinned copper. |
| Jacket: | HD Polyethylene. |
| Diameter: | 0.34 inch, 0.88mm. |
| Shield: | (A) 85% braid 36 AWG tinned copper. (B) mylar 25% overlap rate. |
| Jacket Colors: | White & white/black, red & red/black. |
| Center Conductor: | 0.019 inches, 0.48mm. |
| Dielectric: | 0.076 inches, 1.95mm. |
| Individual Coax: | 0.102 inches, 2.6mm. |
| Impedance: | 75?? |
| DC resistance: | 45??per 1000ft, 148??per km. |
| Capacitance: | 17.3pF per foot, 57pF per meter. |